

Statement of Verification

BREG EN EPD No.: 224

Issue 1

This is to verify that the
Environmental Product Declaration
provided by:
SAS International



is in accordance with the requirements of:
EN 15804:2012+A1:2013

and

BRE Global Scheme Document SD207

This declaration is for:
SAS System 710 Linear Profile

Company Address

Parc Crescent
Waterton Industrial Estate
Bridgend
CF31 3XU



Laura Critien
Operator

13 November 2018
Date of this Issue

13 November 2018
Date of First Issue

10 November 2023
Expiry Date



This Statement of Verification is issued subject to terms and conditions (for details visit www.greenbooklive.com/terms).

To check the validity of this statement of verification please, visit www.greenbooklive.com/check or contact us.

BRE Global Ltd., Garston, Watford WD25 9XX.
T: +44 (0)333 321 8811 F: +44 (0)1923 664603 E: Enquiries@breglobal.com

Environmental Product Declaration

EPD Number: 224

General Information

| EPD Programme Operator | Applicable Product Category Rules |
|---|---|
| BRE Global Watford, Herts WD25 9XX United Kingdom | BRE Environmental Profiles 2013 Product Category Rules for Type III environmental product declaration of construction products to EN 15804:2012+A1:2013 |
| Commissioner of LCA study | LCA consultant/Tool |
| SAS International 31 Sutton Business Park Reading UK RG6 1AZ | BRE LINA Version 2.0.8 |
| Declared/Functional Unit | Applicability/Coverage |
| 1LM of SAS System 710 Linear profiles | Manufacturer specific product average |
| EPD Type | Background database |
| Cradle to Gate with options | ecoinvent v3.2 |
| Demonstration of Verification | |
| CEN standard EN 15804 serves as the core PCR ^a | |
| Independent verification of the declaration and data according to EN ISO 14025:2010 <input type="checkbox"/> Internal <input checked="" type="checkbox"/> External | |
| (Where appropriate ^b)Third party verifier: Nigel Jones | |
| a: Product category rules b: Optional for business-to-business communication; mandatory for business-to-consumer communication (see EN ISO 14025:2010, 9.4) | |
| Comparability | |
| Environmental product declarations from different programmes may not be comparable if not compliant with EN 15804:2012+A1:2013. Comparability is further dependent on the specific product category rules, system boundaries and allocations, and background data sources. See Clause 5.3 of EN 15804:2012+A1:2013 for further guidance | |

Information modules covered

| Product | | | Construction | | Use stage | | | | | | | End-of-life | | | | Benefits and loads beyond the system boundary |
|-------------------------------------|-------------------------------------|-------------------------------------|--------------------------|-----------------------------|--------------------------------|--------------------------|--------------------------|--------------------------|--------------------------|--------------------------|--------------------------|---------------------------|--------------------------|--------------------------|-------------------------------------|---|
| A1 | A2 | A3 | A4 | A5 | Related to the building fabric | | | | | Related to the building | | C1 | C2 | C3 | C4 | D |
| Raw materials supply | Transport | Manufacturing | Transport to site | Construction – Installation | Use | Maintenance | Repair | Replacement | Refurbishment | Operational energy use | Operational water use | Deconstruction demolition | Transport | Waste processing | Disposal | Reuse, Recovery and/or Recycling potential |
| <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input checked="" type="checkbox"/> | <input type="checkbox"/> |

Note: Ticks indicate the Information Modules declared.

Manufacturing site(s)

SAS International
 Waterton Industrial Estate
 Bridgend
 South Wales
 UK

Construction Product:

Product Description

System 710 comprises a powder coated steel rolled profile which simply hooks onto the notched J-bar carrier rail and is a highly cost-effective linear profile option. System 710 is a discontinuous linear profile system intended for use in corridors and shorter run applications between ceiling features. Standard lengths of profile are 3000mm and standard width of 30mm with depths of 60mm and 98mm, longer continuous runs of profile can be achieved by using a splices to join profiles. System710 is a discontinuous linear profile system intended for use in corridors and shorter run applications between ceiling features and is ideally suited to high traffic zones requiring open areas for smoke extraction

Technical Information

Property

System components are manufactured and tested in accordance with BS EN 31964:2014.
Essential Characteristics Performance:
 Reaction to Fire: (up to) A2-S1-D0 European Reaction to Fire classification system (Euroclasses)
 Release of Formaldehyde: CLASS E1
 Release of Asbestos: NO CONTENT
 Sound Absorption: (up to) Single Value $\alpha_w = 1.00$ class A
 Durability: CLASS B

Main Product Contents

The raw material quantities have been taken for all variations of the system and modelled as a single dataset. The main product contents listed below represent the average values derived from this dataset, with a weight of 3.784Kg/LM


| Material/Chemical Input | % |
|--------------------------|-----|
| Steel | 95% |
| Polyester Powder Coating | 5% |

Manufacturing Process

The Bridgend factory is split into two separate units; Unit 1 is where the tile systems are formed, including the addition of the various types of acoustic padding. Key Unit 1 processes include: slitting of the steel/aluminium coils, perforating, washing, spray coating and drying. These processes account for the most energy intensive stages of the products life cycle. Unit 2 is where the grid systems are rolled and formed; it houses less energy-intensive processes than Unit 1.

Process flow diagram

SAS Ceiling Steel Tile Manufacturing Process



Life Cycle Assessment Calculation Rules

Declared / Functional unit description

1LM of SAS System 710 (3.784Kg/LM) - Polyester powder coated steel linear profile for use in ceiling applications.

System boundary

This is a cradle-to-gate with options LCA, reporting all production life cycle stages of modules A1 to A3, and end of life disposal module C4 in accordance with EN15804:2012+A1:2013.

Data sources, quality and allocation

The supporting LCA study was carried out using BRE LINA v2.0.8 using manufacturer specific data provided by SAS International for the production period of the 12 months of 2017. Raw material quantities have been taken from recorded production/manufacture data and product geometry from the Syteline internal production system, for all variations of the SAS 710 linear profile system made in the 12 month period.

SAS International manufacture other products in addition to the System 710 so some allocation of primary data has been carried out. Since the manufacturing steps responsible for slitting, perforating and drying the coated metal are the most energy intensive processes of the site, it is assumed that the gas and electricity consumption is the same for every linear meter (LM) metal product produced. This same allocation was applied to total site water usage. Production waste has been allocated to individual products by applying a percentage wastage rate (based on historical values and used for stock management) to each quantity of raw material. All packaging and non-production waste (waste packaging) has also been allocated using this methodology with applied percentage based on planned/estimated packaging and waste requirements for each product/system/components.

Secondary data has been drawn from the BRE LINA database v2.0.29 and the background LCI datasets are based on ecoinvent v3.2. Upstream extraction and/or processing of inputs are included within the use of the background datasets within LINA. Emissions from fuels used are included within the relevant datasets.

Cut-off criteria

No inputs or outputs have been excluded and all raw materials, packaging and transport, energy, water use and wastes, are included, except for direct emissions to air, water and soil, which are not measured.

LCA Results

Results per declared unit 1LM (3.784Kg/LM) of this SAS System 710, for the declared modules can be found in the following:

(MND = module not declared; MNR = module not relevant; INA = indicator not assessed; AGG = aggregated)

| Parameters describing environmental impacts | | | GWP | ODP | AP | EP | POCP | ADPE | ADPF |
|---|--------------------------|------|---------------------------|------------------|---------------------------|--|---|--------------|--------------------------|
| | | | kg CO ₂ equiv. | kg CFC 11 equiv. | kg SO ₂ equiv. | kg (PO ₄) ³⁻ equiv. | kg C ₂ H ₄ equiv. | kg Sb equiv. | MJ, net calorific value. |
| Product stage | Raw material supply | A1 | 9.27 | 6.86e-7 | 1.04e-1 | 3.87e-2 | 1.00e-2 | 1.22e-3 | 1.31e+2 |
| | Transport | A2 | 9.36e-2 | 1.76e-8 | 3.18e-4 | 8.41e-5 | 6.25e-5 | 1.98e-7 | 1.44 |
| | Manufacturing | A3 | 4.53 | 6.22e-7 | 3.33e-2 | 8.73e-3 | 2.95e-3 | 1.47e-5 | 1.15e+2 |
| | Total (of product stage) | A1-3 | 1.39e+1 | 1.32e-6 | 1.38e-1 | 4.75e-2 | 1.30e-2 | 1.24e-3 | 2.47e+2 |
| | Disposal | C4 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |

GWP = Global Warming Potential;
 ODP = Ozone Depletion Potential;
 AP = Acidification Potential for Soil and Water;
 EP = Eutrophication Potential;

POCP = Formation potential of tropospheric Ozone;
 ADPE = Abiotic Depletion Potential – Elements;
 ADPF = Abiotic Depletion Potential – Fossil Fuels;

LCA Results (continued)

| Parameters describing resource use, primary energy | | | PERE | PERM | PERT | PENRE | PENRM | PENRT |
|--|--------------------------|------|---------|---------|---------|---------|-------|---------|
| | | | MJ | MJ | MJ | MJ | MJ | MJ |
| Product stage | Raw material supply | A1 | 9.67 | 2.49e-4 | 9.67 | 1.38e+2 | 0 | 1.38e+2 |
| | Transport | A2 | 2.13e-2 | 6.24e-8 | 2.13e-2 | 1.43 | 0 | 1.43 |
| | Manufacturing | A3 | 4.40e+1 | 2.00e-5 | 4.40e+1 | 1.41e+2 | 0 | 1.41e+2 |
| | Total (of product stage) | A1-3 | 5.37e+1 | 2.69e-4 | 5.37e+1 | 2.80e+2 | 0 | 2.80e+2 |
| | Disposal | C4 | 0 | 0 | 0 | 0 | 0 | 0 |

PERE = Use of renewable primary energy excluding renewable primary energy used as raw materials;
 PERM = Use of renewable primary energy resources used as raw materials;
 PERT = Total use of renewable primary energy resources;

PENRE = Use of non-renewable primary energy excluding non-renewable primary energy resources used as raw materials;
 PENRM = Use of non-renewable primary energy resources used as raw materials;
 PENRT = Total use of non-renewable primary energy resource

LCA Results (continued)

| Parameters describing resource use, secondary materials and fuels, use of water | | | | | | |
|---|--------------------------|------|----|---------------------------|---------------------------|----------------|
| | | | SM | RSF | NRSF | FW |
| | | | kg | MJ net calorific value | MJ net calorific value | m ³ |
| Product stage | Raw material supply | A1 | 0 | 0 | 0 | 2.41e-1 |
| | Transport | A2 | 0 | 0 | 0 | 3.31e-4 |
| | Manufacturing | A3 | 0 | 0 | 0 | 4.44e-2 |
| | Total (of product stage) | A1-3 | 0 | 0 | 0 | 2.86e-1 |
| | Disposal | C4 | 0 | 0 | 0 | 0 |

SM = Use of secondary material;
RSF = Use of renewable secondary fuels;

NRSF = Use of non-renewable secondary fuels;
FW = Net use of fresh water

LCA Results (continued)

| Other environmental information describing waste categories | | | | | | |
|---|--------------------------|------|---------|---------|---------|--|
| | | | HWD | NHWD | RWD | |
| | | | kg | kg | kg | |
| Product stage | Raw material supply | A1 | 2.01 | 8.68e-1 | 3.11e-4 | |
| | Transport | A2 | 5.78e-4 | 1.05e-1 | 9.96e-6 | |
| | Manufacturing | A3 | 3.36e-2 | 2.26e-1 | 6.43e-4 | |
| | Total (of product stage) | A1-3 | 2.04 | 1.20 | 9.64e-4 | |
| | Disposal | C4 | 0 | 0 | 0 | |

HWD = Hazardous waste disposed;
NHWD = Non-hazardous waste disposed;
RWD = Radioactive waste disposed

LCA Results (continued)

| Other environmental information describing output flows – at end of life | | | | | | |
|--|--------------------------|------|-----|---------|-----|-----------------------|
| | | | CRU | MFR | MER | EE |
| | | | kg | kg | kg | MJ per energy carrier |
| Product stage | Raw material supply | A1 | 0 | 0 | 0 | 0 |
| | Transport | A2 | 0 | 0 | 0 | 0 |
| | Manufacturing | A3 | 0 | 3.69e-1 | 0 | 0 |
| | Total (of product stage) | A1-3 | 0 | 3.69e-1 | 0 | 0 |
| | Disposal | C4 | 0 | 3.78 | 0 | 0 |

CRU = Components for reuse;
MFR = Materials for recycling

MER = Materials for energy recovery;
EE = Exported Energy

Scenarios and additional technical information

| Scenarios and additional technical information | | | |
|--|--|-------|---------|
| Scenario | Parameter | Units | Results |
| C4 disposal at end of life | It is assumed that as the main element of the SAS 710 system is steel and a valuable material, 100% of the product is recycled at end of life. | | |

References

BSI. Sustainability of construction works – Environmental product declarations – Core rules for the product category of construction products. BS EN 15804:2012+A1:2013. London, BSI, 2013.

BSI. Environmental labels and declarations – Type III Environmental declarations – Principles and procedures. BS EN ISO 14025:2010 (exactly identical to ISO 14025:2006). London, BSI, 2010.

BSI. Environmental management – Life cycle assessment – Principles and framework. BS EN ISO 14040:2006. London, BSI, 2006.

BSI. Environmental management – Life cycle assessment – requirements and guidelines. BS EN ISO 14044:2006. London, BSI, 2006.

BS EN 31964:2014 Suspended Ceiling requirements and tests methods